

# CHALLENGER **Trailer-mounted Rigs**

Well Servicing • Workover • Drilling

### CHALLENGER


- · With straight deck for 230 drilling floor, or
- · with elevated substructure to accommodate BOP stack

### **Drilling Capacity:**

31/2-in. Drillpipe 5,000 ft. 41/2-in. Drillpipe 3,000 ft.

Maximum Hook Load:

100,000 lbs. on 6 lines



W/Short WETOK GOSS 112 000 Lbs 12.5 ONly

### CHALLENGER


- · With straight deck for drilling floor, or
- · with elevated substructure to accommodate BOP stack

## Drilling Capacity:

31/2-in. Drillpipe 5,000 ft. 41/2-in. Drillpipe 4,000 ft.

Maximum Hook Load:

150,000 lbs. on 6 lines



## CHALLENGER

· With elevated substructure to accommodate BOP stack

### **Drilling Capacity:**

31/2-in. Drillpipe 7,500 ft. 41/2-in. Drillpipe 6,500 ft.

Maximum Hook Load:


240,000 lbs. on 6 lines

<b>Basic Specifications</b>	230	321	361
Axles	Two @ 18,000 lbs.;	Two @ 18,000 lbs.;	Two @ 18,000 lbs.;
	Optional Floating Third	Optional Floating Third	Optional Floating Third
Drawworks	Double Drum Stacked	Double Drum Stacked	Double Drum Stacked
Hoisting	10 <sup>1</sup> / <sub>2</sub> ins. x 24 ins.	10 <sup>1</sup> / <sub>2</sub> ins. x 23 <sup>1</sup> / <sub>2</sub> ins.	, 16 ins. x 221/2 ins.
Kelly	10 <sup>1</sup> / <sub>2</sub> ins. x 21 <sup>7</sup> / <sub>8</sub> ins.	10 <sup>1</sup> / <sub>2</sub> ins. x 23 <sup>1</sup> / <sub>2</sub> ins.	16 ins. x 22 <sup>1</sup> /2 ins.
Single Line Pull	23,000 lbs. maximum	30,000 lbs. maximum	45,000 lbs. maximum
Drum Brakes	8 ins. x 32 ins.	8 ins. x 32 ins.	8 ins. x 38 ins.
Engines <sup>(1)</sup>	Compounded 4-71N Detroit Diesel	Compounded 6-71N Detroit Diesel	Compounded 8V92N Detroit Diesel
Operating Equipment	3-sheave 17-in. 75-ton Hook Hoisting;	3-sheave 17-in. 75-ton Hook Hoisting;	3-sheave 24-in. 125-ton Hook Hoisting;
	3-sheave 17-in. 75-ton Block	3-sheave 17-in. 75-ton Block	3-sheave 24-in. 125-ton Block
Derrick Height	64 ft.	64 ft.	. 84 ft.
Crown Sheaves	17-ins. dia. for <sup>7</sup> /8-in. line	17-ins. dia. for <sup>7</sup> /8-in. line	24 ins. dia. for 1-in. line
Dimensions (road)	L. 74 ft., H. 14 ft., W. 8 ft.	L. 74 ft., H. 14 ft., W 8 ft.	L. 89 ft., H. 15 ft., W. 10 ft.

23 W/gourd\_

21 No gourd

"Or operator's choice of equivalent engine



For Inquiries, Quotes, or to Order Parts, Please Contact

### Cooper Manufacturing Corp.

A Tulsa Industries, Inc. company

1221 E. Houston Broken Arrow, Oklahoma 74012 Telephone 918-258-7300 Fax 918-258-7302